







Choose from mechanical galvanized or 300 series stainless steel options in 1-1/2", 2" or 2-1/2" sizes when looking to replace nails or screws that have failed. The sharp point drills easily and the oversized 5/8" EDPM washer seals tightly. Fasten aluminum panels effortlessly using the SS screw. Quick ship colors available or match to your roof color.







ITEM#	DESCRIPTION	HEAD STYLE	DRILL POINT	PCS/BOX	LB/BOX
12112RGSS	#12 × 1 - 1/2"	1/4 Hex	SP	2,000	31.4
122RGSS	#12 × 2"	1/4 Hex	SP	1,500	28.7
12212RGSS	#12 × 2 - 1/2"	1/4 Hex	SP	1,000	22.8

PULL OUT STRENGTH

SUBSTRATE	PENETRATION	PULL OUT STRENGTH	
3/4" Ply	Full	528	
1/2" Ply	Full	338	
7/16" OSB	Full	191	
2 x Yellow Pine	1"	756	
2 x Spruce Pine Fir	1"	745	
2 x Spruce Pine Fir	1 - 1/2"	926	

SHEAR				
2,000				
TENSILE				
2,206				
TORSIONAL				
98				



PULL OVER STRENGTH

SUBSTRATE	GAUGE	THICKNESS	PULL OVER STRENGTH
AZ55 Galvalume	29	0.014	427
AZ55 Galvalume	26	0.018	622
AZ55 Galvalume	24	0.024	952

ALSO AVAILABLE:









